

# Find the 1600 for you!



FEATURES:	1600P	1600P-DBX	1600P-DB
800 -1,600 SPM (MINIMUM SPEED: 60 SPM)	X	X	X
SIMULTANEOUS BOBBIN WINDING	X	X	X
KNEE LIFT	X	X	X
PRESSURE INDICATOR WINDOW	X	X	X
AUTO THREAD CUTTER	X	X	
VARIABLE SPEED CONTROL	X	X	X
NEEDLE THREADER	X		
HL NEEDLE	X		
DB NEEDLE		X	X
SIDE-LOADING, INDUSTRIAL ROTARY HOOK	X	X	X
MEMORIZED NEEDLE UP/DOWN	X	X	X
EXTRA LARGE 8.85" X 5.5" WORK AREA	X	X	X
DUAL LIGHTS	X	X	X
INDUSTRIAL-TYPE THREAD TAKE-UP LEVER	X	X	X
NO OIL HOLES ON BED	X	X	X
SEALED BEARINGS ON SHAFTS	X	X	X
UP TO 11 LBS. OF PRESSER FOOT PRESSURE	X	X	X
INDUSTRIAL PRETENSION THREADING	X	X	X
THREAD DIAGRAM PRINTED ON MACHINE FRONT	X	X	X
BOBBIN WINDING DIAGRAM PRINTED ON MACHINE TOP	X	X	X
LIQUID RESPONSE FOOT CONTROL - NO STALLS	X	X	X
SYNCHRONIZED THREAD TENSION LEVER	X	X	X
VARIABLE STITCH LENGTH UP TO 6MM	X	X	X
METAL ATTACHMENT SETTING PLATE	X	X	X
SLEEK DESIGN OF HOME MACHINE	X	X	X
QUIET OPERATION WITH NO EXTERNAL MOTOR	X	X	X
DUST COVER	X	X	X
OPTIONAL EXTENSION TABLE AVAILABLE	X	X	X

Janome Sewing Machine Co., Ltd.

1-1 Kyobashi 3-chome, Chuo-Ku, Tokyo 104-8311, Japan

Tel: +81-3-3277-2033 Fax: +81-3-3281-1160

E-mail: [support@gm.janome.co.jp](mailto:support@gm.janome.co.jp)