



5000CD

DENTAL LAB STEAM CLEANER

The 5000CD produces 50 PSI of steam pressure and reaches temperatures up to 221° F at the tip. It's ideally suited for use in dental labs for cleaning away left over wax, plaster waste and other debris, and for polishing the final product.

Steam deodorizes and sanitizes with heat and moisture and since the only ingredient required for the 5000CD is water, cleaning has never been safer, healthier or more environmentally friendly.

SPECIFICATIONS

ELECTRICAL	120V	
WATER CAPACITY	.66 GAL	2.5L
OPERATING PRESSURE	50 PSI	
STEAM TEMPERATURE	221°F	105°C
ELEMENTS	1 - 1000W	
POWER CONSUMPTION	8 amps	
TANK CONSTRUCTION	Stainless steel	
LOW WATER INDICATOR	Standard	
STEAM CONNECTOR TYPE	Quick-release	
NET WEIGHT	13.25 lb	6 kg
SHIPPING WEIGHT	15.5 lb	7 kg
PRODUCT DIMENSIONS	14" x 8.75" x 11"	35.5 x 22 x 28 cm
SHIPPING DIMENSIONS	16" x 12.25" x 16"	40.5 x 31 x 40.5 cm
ELECTRICAL APPROVAL	cETLus	
WARRANTY	Limited 1 year, 2 year boiler tank	

THE POWER OF STEAM



4 SAFETY SYSTEMS



STAINLESS STEEL TANK



PRESSURE GAUGE



MADE IN ITALY



COMPLETE ACCESSORY KIT



BOILER TANK 2 YEAR WARRANTY



THERMOSTAT RESET



3.5 BAR PRESSURE



5000CD

DENTAL LAB STEAM CLEANER

