



6000CD

DENTAL LAB STEAM CLEANER

The 6000CD produces 60 PSI of steam pressure and reaches temperatures up to 221° F at the tip. It's ideally suited for use in dental labs for cleaning away left over wax, plaster waste and other debris, and for polishing the final product.

Steam deodorizes and sanitizes with heat and moisture and since the only ingredient required for the 6000CD is water, cleaning has never been safer, healthier or more environmentally friendly.

SPECIFICATIONS

ELECTRICAL	120v	
WATER CAPACITY	1.25 GAL	4.5L
OPERATING PRESSURE	60 PSI	4.1 BAR
STEAM TEMPERATURE	221°F	105°C
ELEMENTS	1 - 1,200 watt	
POWER CONSUMPTION	10 amps	
TANK CONSTRUCTION	Stainless steel	
LOW WATER INDICATOR	Standard	
STEAM CONNECTOR TYPE	Quick-release	
NET WEIGHT	16.7 lb	7.5 kg
SHIPPING WEIGHT	23 lb	10.4 kg
PRODUCT DIMENSIONS	13" x 8.75" x 15"	33 x 22 x 38 cm
SHIPPING DIMENSIONS	15.5" x 12" x 17.5"	39 x 30.5 x 44.5 cm
ELECTRICAL APPROVAL	cETLus	
WARRANTY	Limited 1 year, 2 year boiler tank	

THE POWER OF STEAM



4 SAFETY SYSTEMS



STAINLESS STEEL TANK



PRESSURE GAUGE



MADE IN ITALY



BLOW DOWN VALVE



BOILER TANK 2 YEAR WARRANTY



THERMOSTAT RESET



4.1 BAR PRESSURE



6000CD

DENTAL LAB STEAM CLEANER

